

1150 watt wet stone polisher with variable speed, plug for isolating transformer, 115 mm

LE 12-3 100 WET

Order number 368.660



Technical attributes	
Max. tool Ø	115 mm
No load speed	1200-3700 rpm
Power input	1150 watt
Power output	700 watt
Tool fixture	M 14
Cable length	5,0 m
Size (W x L x H)	350 x 110 x 140 mm
Weight	2,4 kg

Standard equipment	
1 bail handle	368.709
1 hook-and-loop cable ties	364.169

1150 watt wet stone polisher with variable speed, plug for isolating transformer, 115 mm

- + Powerful 1150 W motor
- + Microprocessor electronics: with tachogenerator constant speed control, soft start, overload protection and speed selection
- + Contour plug: can be connected only to an isolating transformer. For safety reasons, operation is permitted only connected to the FLEX TT 2000 isolating transformer
- + High torque for maximum material removal and optimum surface quality
- + The water feed and control system is located below the housing, which makes operation and precise dosing easy. An unobstructed grip area is provided directly above the backing pad
- + 2 m special hose: No additional hose safety devices required. Increases flexibility, reduces weight and prevents risk of injury from hose clips
- + Quick-fit brass coupling: for 1/2" water hose
- + Powder-coated and varnished magnetic pad for a long service life, thanks to the additional protection against wear and abrasive dust
- + Grip hood for easy handling and precise working
- + Bail handle: Secure grip, even when working on vertical surfaces
- + Spindle lock
- + This machine is also available in 110 V